PATENT SPECIFICATION

(11) **1362365**


(21) Application No. 36564/70 (22) Filed 28 July 1970

(23) Complete Specification filed 12 July 1971

(44) Complete Specification published 7 Aug. 1974

(51) International Classification C07G 7/02

(52) Index at acceptance C3H 3





(54) IMPROVEMENTS IN OR RELATING TO THE PRODUCTION OF ENZYME PREPARATIONS

TERAPEUTISK (71) We, NOVO LABÓRATORIUM A/S, a Danish company of 115, Nordre Fasanvej, 2200 Copenhagen N, Denmark, do hereby declare the invention for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:-

This invention relates to a process for the 10 production of enzyme preparations consisting

of uniformly sized solid spheres. In this specification and in the claims the expression "pellets" is intended to cover not only normal pellets, but also extruded, shaped 15 bodies normally having an elongate structure,

e.g. a spaghetti-like structure.

It is known to convert an extruded material into uniformly sized solid spheres by supplying the extruded pellets to a container with stationary solid side walls and a rotatably mounted bottom friction plate roratable with a speed of from about 100 and up to 1800 rpm. This spheroidising is caused by centrifugal force and friction and has been performed in machines sold under the Trade Name MARUMERIZER obtained from the Eli Lilly Company and manufactured by Fuji Denki Kogyo Company, Osaka, Japan. The word MARUMERIZER is a Trade Mark.

We have now found that this spheroidising process is very useful in connection with enzyme preparations, particularly for use in the detergent industry, e.g. preparations comprising enzymes and additives normally used 35 in washing and cleaning compositions, when the process is carried out with certain extruded enzyme-containing pellets. These pellets are produced in a conventional manner from a mixture of 75%, to 97% of a solid enzyme-containing powder and 25% to 3%, of water.

Accordingly, the process of the invention comprises subjecting enzyme-containing pellets

prepared by extrusion from a mixture containing from 75 to 97 weight per cent of a solid enzyme-containing powder, comprising, if desired, an enzyme stabiliser, and from 25 to 3 weight per cent of water to a spheroidising process using a rotational speed of up to 2000 rpm in an apparatus causing centrifugal and frictional forces to be applied to the said pellets, whereafter, if desired, the solid spheres produced are subjected to a fluid-bed drying operation.

The enzyme preparations which can be produced by the process of this invention consist of particles of practically uniform size suitable for the intended industrial uses. The particles are substantially dust-free and show a sufficient mechanical strength for handling without the formation of dust. The particles also show sufficient flow properties for transportation in factories.

In the following examples rotational speeds of up to about 800-1000rpm are used during the spheroidisation, but speeds up to 2000 rpm may be employed.

In accordance with a preferred embodiment of the invention the spheroidising process is carried out in a machine of the type marketed under the Trade Name MARUMERIZER referred to above.

The product prepared by the process of the invention is easily soluble in hot as well as cold water. This is of special advantage when an enzyme product is to be used as an additive to a prewashing agent or a soaking agent.

The products of the present process possess a good storage stability, even under unfavourable conditions as regards temperature and humidity, and also when these products are used in perborate-containing washing agents.

If desired the products prepared in accordance with the invention may be further improved by coating in a manner known per se with a

[Price 25p]

POOR QUALITY

tablet coating composition, e.g. as described in J. Am. Pharm. Association, Aug. 1954, Vol. XLIII, No. 8. Preferably the coating is carried out using a waxy substance, if desired a slightly sticky substance, but the coating agent should be easily soluble or dispersable in water.

Examples of preferred coating materials are as mentioned in the above literature polyethyleneglycol 6000 to 1000, but also nonylphenolpolyglycol-ethers having from 16 to 50 ethyleneglycol units, ethoxylated fatty alcohols in which the hydrocarbon moiety of the alcohol contains from 12 to 20 carbon atoms and the polyglycol moiety comprises from 15 to 80 polyethyleneglycol units, fatty alcohols, fatty acids and monoand diesters of fatty acids and glycerol.

The optional coating process of the invention may be carried out in a simple and inexpensive apparatus, such as a mixing apparatus of the drum type having rotatable mixing aggregates. Thus, the use of complicated and expensive special kettles or fluidising units comprising nozzle arrangements can be avoided. Furthermore, it is often possible merely to melt the coating material and pour or spray it into the mixing drum, thus avoiding special solution processes.

The coated products are suitable for colouring with e.g. titanium dioxide or pigment colours, and the coated products are also properly protected against possible abrasion giving rise to the formation of undesirable enzyme-containing dust.

The enzyme-containing powder in addition to the enzyme itself preferably contains suitable additives, such as lubricants, fillers, binders and enzyme stabilisers. Polyethyleneglycols are examples of suitable lubricants, and examples of fillers are inorganic salts, for instance sodium chloride and sodium sulfate, pentasodium tripolyphosphate. tetrasodium pyrophosphate or the corresponding potassium salts, cellulose powder, starch powder, cellu-45 lose derivatives, starch decomposition products, starch derivatives, gelatine, casein, skimmed milk powder, polyvinyl alcohol and polyvinylpyrrolidones. Some of these substances may also act as binders. This applies for instance 50 to the starch decomposition product dextiin, polyvinylpyrrolidone and polyvinyl alcohol. Gelatine, starch decomposition products, and other substrates for the enzymes and polyvinylpyrrolidone are examples of enzyme 55 stabilizers. In particular, casein, skimmed milk powder and polyvinylpyrrolidone have been found to be useful.

Furthermore, polyvinylpyrrolidone acts in such a manner that each single string of extrudate becomes less adhesive so that the tendency to string adhesion in the spheroidising process is lowered.

In the spheroidising steps it can be advantageous to use a powdering agent to prevent any tendency of adherence between the spheroidising particles. Examples of such powdering agent are inorganic salts, such as anhydrous sodium sulfate, and inorganic oxides such as titanium dioxide.

The ratio between the enzyme powder and water in the mixture to be spheroidised depends on the enzymatic activity of the enzyme powder and the desired enzyme product.

The following Examples illustrate the process of the invention. In some of these Examples we have used an enzyme concentrate called ALCALASE (the "ALCALASE" is a Trade Mark), which is a commercial product and contains a proteolytic enzyme together with some inactive organic matter and some inorganic salts, mainly sodium sulphate. In an example, we have also used an enzyme concentrate TERMOZYM (the word "TERMOZYM" is a Trade Mark), which is a commercial product and contains an amylolytic enzyme together with some inactive organic matter and some inorganic salts, mainly sodium sulphate.

Furthermore, the working Examples comprise examples showing the use of hemicellulose, fungal α-amylase as well as a proteolytic enzyme called ENZYME X and produced as described in our co-pending Cognate Application Nos. 45046/67 and 35921/68 (Serial No. 1,243,784) by cultivation of the Bacillus strain NCIB No. 10147 (NCIB No. 10147 is a deposit number for the said strain at the National Cellection of Industrial Bacteria, Torry Research Station, Aberdeen, Scotland). Apart from the ENZYME X there may be used similar proteolytic enzymes prepared by aerobic cultivation of protease-forming species of the genus Bacillus on a nutrient medium 105 having a pH within the range of 9 to 11 and maintaining during the main period of cultivation a pH in the said medium between 7.5 and 10.5, the said proteolytic enzymes showing a proteolytic activity of 80 to 100 110 per cent of maximum activity when measured at pH 12 by the Anso hemoglobin method carried out in the presence of urea. Furthermore, other amylases and proteinases, as well as milk-coagulating enzymes, cellulases, iso- 115 merases, e.g. glucose isomerase, pectinases, amylglucosidase and B-glucanase may be

Example 14 is by way of comparison only. The percentages in the Examples are per 120 cent by weight.

Example 1.

There is produced a premix consisting of 30% of ALCALASE and 70% of sodium sulphate, and this mixture is moistened in a 125 mixing aggregate with 8% of water which is sprayed on the mixture.

The moistened mixture is extruded in the conventional manner through a 0.7 mm screen,

70

Bulk weight

and the pellets formed are then spheroidised in a MARUMERIZER at a starting speed of 400 rpm while powdering with 3% of titanium dioxide and finally at a speed of 800 rpm. Any traces of dust from the powdering substance can be removed by screening. The final product has the following pro-

perties:

1.3 Anson units/g Proteolytic activity 0.7 mm 10 Particle size about 1.0 g/cm³ Bulk weight

The product is dust-free and soluble in aqueous media.

Example 2. A premix consisting of 30% ALCALASE and 70% sodium chloride is moistened with 6% of water and extruded and spheroidised as described in Example 1. The final product has the same properties as those mentioned in connection with the final product produced in Example 1.

> Example 3. A premix having the following composition

25% ALCALASE 25 10% Dextrin 5% Cellulose powder 6% Polyethyleneglycol 6000 54% Anhydrous sodium sulfate

is moistened with 8% of water, and the ±0 moistened mixture is extruded in the conventional manner through a 0.8 mm screen. The pellets formed are spheroidised as in Example 1, except that anhydrous sodium sufphate is used as powdering agent instead of 35 titanium dioxide.

The final product has the following properties:

Proteolytic activity 1.0 Anson units/g . 0.8 mm Particle size Bulk weight about 1.0 g/cm³

Example 4.

A premix consisting of 25% of ALCA-LASE, 10% of cellulose powder and 65% of sodium sulphate is moistened with 17.5%, 45 of an aqueous solution containing 10% of hydroxypropyl-cellulose and 2% of polyethyleneglycol 6000.

The moistened mixture is extruded and spheroidised as in Example 1, and the final product has the same properties as those mentioned in connection with the final product produced in Example 3.

Hydroxypropyl-cellulose may be substituted by polyvinyl-pyrrolidone.

55

Example 5 A mixture consisting of 33.5% of ALCA- LASE, 25% of TERMOZYM, 18% of dextrin, 18.5% of cellulose powder and 5% of polyethyleneglycol 6000 is moistened with 16% of water and extruded in the conventional manner through a 0.8 mm screen. The pellets formed are then spheroidised as described in Example 1. The final product has the following 65 properties: Proteolytic activity 1.3 Anson units/g Amylolytic activity 135 SKB units/g 0.8 mm Particle size

Example 6. A powder mixture of the composition:

25% ALCALASE 10% Cellulose powder 3% Gelatine 60% Anhydrous sodium sulfate 2% Polyethyleneglycol 6000 75

0.9 g/cm³

is moistened with 16% of water and is extruded and spheroidised as described in Example 3. The final product has the same properties as those mentioned in connection with the product produced in Example 3.

Example 7. A powder mixture of the composition

6.5% ALCALASE 10.9% Skimmed milk powder 82.6% Sodium chloride 85

was moistened with 18.5% of a solution of the composition

53% Water 35% Polyethyleneglycol 6000 12% Polyvinylpyrrolidone 90

The wetted mixture was extruded and spheroidised as described in Example 3.

The spheroidised product was fluid-bed dried at 40 to 60° C to a moisture content of about 0.5%.

The final product has the following properties:

0.3 AU/g 0.7 mm Proteolytic activity 100 Particle size 1.05 g/cm³ Bulk density Soluble in water

Example 8. Powder mixtures of the composition

5.5% ALCALASE 5.5% or 11% Casein 89% or 84.5% Sodium chloride 105

were moistened with 18.5% of a solution of the composition

_			
5	53% Water 35% Polyethyleneglyco 12% Polyvinylpyrrolid The wet mixture was ext as described in Example 3.	one	was moistened with 7% of water and extruded through a 0.9 mm screen and spheroidised at 900 rpm. The wet product was fluid-bed dried at 40° C to a moisture content below 1%. The properties of the final product were
	Example 9 A premix of the composi 3.0% ENZYME X strain NCIB No	ition (pr e pared from	Enzymatic activity 50,000 VHCU/g Particle size 0.9 mm Bulk density 0.8 g/cm ³ Water soluble
10	2.0% Polyvinylpyrrolid 6.0% Polyethyleneglyco 89% Sodium chloride was moistened with 8% of extruded through a 0.9	lone ol (6000) f water and then mm screen and	VHCU represents Viscosity Hemicellulose Units. The VHC method is a viscometric method, measuring the reduction of viscosity of a substrate made from locust bean gum under standard conditions. The viscosity is measured with an Ubbelohde viscometer.
15	The wet product was flumoisture content of approxi	id-bed dried to a imately 0.5%.	Example 12.
20	The properties of the final Proteolytic activity Particle size appr. Bulk density appr.	l product were 1 KNPU/g 0.8 mm 1.1 g/cm³	A premix of the composition 35% Fungala-amylase 63% Sodium chloride 2% Polyvinylpyrrolidone
25	Water soluble KNPU represents Kilo I Units. One NOVO-proceinas as that amount of enzyme w dard conditions, hydrolyses	thich, under stan- casein at such	is moistened with 12% of water and extruded through a 0.8 mm screen and spheroidised at a speed of 800 rpm. The spheroidised product was fluid-bed dried at 50° C, and the final product had the following properties
30	a rate that the initial rate peptides giving a colour wit tri-nitrobenzene sulphonic accorresponds to 1 amole glycidard conditions are: 0.5% Hin (Merck) in 0.05 M borate (measured at 20°C) reacting at 50°C.	th TNBS (2,4,6- cid-1-Na-reagent) ne/minute. Stan- lammarsten case- buffer at pH 9.0	Enzymatic activity 1000 FAU/g Particle size 0.7 mm Bulk weight about 0.9 g/cm³ Example 13. A premix of the composition 8
35	Example 10. A premix of the composition		26% ALCALASE 4% PLURONIC L 61 70% Sodium tripolyphosphate (MARCHON type d)
.0	12% ALCALASE 5% Polyethyleneglycol 1% Polyvinylpyrrolidon 84% Sodium citrate	6000	was moistened with 12.5% of water and extruded through a 0.9 mm screen. The words "PLURONIC" and "MARCHON" are Trade Marks.
	was moistened with 9.3 / of truded, spheroidised and drie in Example 9. The properties of the final	ed as described	The extrudate was spheroidised as described in Example 3. The final product had the following properties
5	Proteolytic activity Particle size Water soluble	0.5 AU/g 0.7 mm	Proteolytic activity Particle size 0.9 mm Bulk density Soluble in water 1.0 AU/g 0.9 mm 100
	Example 11. A premix of the compositio	n	Example 14. A premix of the composition
)	2% Hemicellulose 6% Polyethyleneglycol 6 2% Polyvinylpyrrolidone 90% Glucose	000	Bacterial amylase 15% Polyethyleneglycol 6000 6% 105 Polyvinylpyrrolidone 2% Sodium chloride 77%

was moistened with 5% of water and extruded through a 0.9 mm screen. The extrude was treated in the MARUMERIZER to form "nuddles" each having a length of 1 to 3 mm.

Enzymatic activity 250 KNE/g Particle size: Small cylinders having rounded-off end faces:

 $0.8 \text{ mm} \times 1 - 3 \text{ mm}$ Bulk density about 1 g/cm³

The granulate was dried in a fluid-bed at temperatures 40° C→60° C.

In the above Example, the treatment in the MARUMERIZER was carried out for about 2 minutes and this is the reason why the particles 15 did not attain spherical form.

When the enzyme preparations prepared by the present process are intended for washing purposes, experiments made demonstrate that the storage stability in washing agents wherein enzyme preparation is present in the form of a finished, dried product is satsifactory, in particular when the enzyme stabilisers re-

ferred to in the foregoing are used.

The following residual activity tables including the references are in respect of finished, dried products prepared according to the invention, except only that the comp Example represents powdered and not lated ALCALASE not being spheroidised references are in accordance with the vant Example except that the conven substrate component for the enzyme has been omitted.

parison	
granu-	
d. The	
rele-	30
ntional	
e heen	

Storage stability in perborate-containing washing agent prepared on the basis of ·	Residual Activity on storing at 30°C; 70% rel. humidity for the periods shown. Method of analysis: TNBS				
	2 weeks	4 weeks	6 weeks	8 weeks	
Example 7				 	
(10.9% skimmed milk powder)	92%	74%	63%	62%	
Reference to Example 7					
6.5% ALCALASE					
2% PVP		60%	52%	49%	
6% PEG 6000	84%				
Balance NaCl					

	Residual Activity on storing 35°C; 67% rel. humidity for the periods shown. Method of analysis: TNBS				
	1 week	2 weeks	4 weeks	6 weeks	
Example 7				 -	
(10.9% skimmed milk powder)	93%	78%	65%	_	
Reference to Example 7	73%	65%	47%		
Example 8					
(11° Casein)	_	75%	64%	51%	
Example 8					
(5.5% Casein)	<u> </u>	72%	54%	43%	
Reference to Example 8	-	29%	24%		
Comparison Example:					
ALCALASE, powdered ungranulated (double test)	-	30%	14%	13%	

In the foregoing, the proteolytic activities have been determined by the Anson-method described in J.Gen.Physiol, 22, 79-89 (1938). The TNBS-method for determining protease activity is described in J.Am.Oil Chem. Soc., 46:81 (1969). a-amylase activities have been determined according to Cereal Chemistry 16, 712 (1939), but with some modifications: thus, the following equations can be used for calculations:

> 1000 SKB units (pH 5.7)~53000 NOVO units for bacterial a-amylase and 1000 SKB units (pH 4.7)-37 FA units for fungal amylase

Hemicellulase activity has been determined viscosimetrically.

WHAT WE CLAIM IS:-

15

1. A process for the production of an 20 enzyme preparation consisting of uniformly sized solid spheres, which process comprises subjecting enzyme-containing pellets prepared by extrusion from a mixture containing from 75 to 97 per cent by weight of a solid enzyme-25 containing powder comprising, if desired, an enzyme stabiliser, and from 25 to 3 per cent by weight of water to a spheroidising process using a rotational speed of up to 2000 rpm in an apparatus causing centrifugal and frictional forces to be applied to the said

2. A process according to Claim 1, wherein the solid spheres produced are subjected to a fluid-bed drying operation.

3. A process according to Claim 1 or 2, wherein the spheroidising process is carried out using a powdering agent preventing adhesion between the spheroidised particles.

4. A process according to Claim 3, wherein the powdering agent is an inorganic salt or an inorganic oxide.

5. A process according to any one of the preceding claims, wherein the spheroidising process is carried out in a machine having a cylindrical container with a stationary solid side wall and a rotatably mounted bottom friction plate rotatable at a speed up to 1800 r.p.m.

6. A process according to any one of the preceding claims, wherein the solid enzyme powder used comprises, as an enzyme stabiliser, (a) polyvinylpyrrolidone and (b) gelatine, casein, skimmed milk powder or other conventional substrate component for the enzyme(s).

7. A process according to any one of the preceding claims, wherein there is employed an enzyme powder wherein the enzyme is a protease, an amylase, an amyloglucosidase or and isomerase.

8. A process according to any one of Claims 1 to 6, in which there is employed an enzyme powder wherein the enzyme is a powdered bacterial proteinase prepared from

65

Bacillus licheniformis, a powdered amylase prepared from Bacillus subtilus, hemicellulase, fungal a-amylase or a proteolytic enzyme prepared by aerobic cultivation of protease-forming species of the genus Bacillus on a nutrient medium having a pH within the range of 9 to 11 and maintaining during the main period of cultivation a pH in the said medium between 7.5 and 10.5, the said proteolytic 1' enzymes showing a proteolytic activity of 80 to 100 per cent of maximum activity when measured at pH 12 by the Anson hemoglobin method carried out in the presence of urea.

9. A process according to any one of the 15 preceding claims, wherein the enzyme-containing end product is coated with a tablet coating composition in a manner known per se.

10. A process according to Claim 9, wherein the end product is coated in a mixing apparatus of the drum type having rotatable mixing

11. A process for the production of an enzyme preparation, in accordance with Claim 1 and substantially as described in foregoing 5 Example 1.

12. A process for the production of an enzyme preparation, in accordance with Claim 1 and substantially as described in foregoing Example 2.

13. A process for the production of an enzyme preparation, in accordance with Claim 1 and substantially as described in foregoing Example 3.

14. A process for the production of an 35 enzyme preparation, in accordance with Claim 1 and substantially as described in foregoing Example 4.

15. A process for the production of an enzyme preparation, in accordance with Claim -50 1 and substantially as described in foregoing Example 5.

16. A process for the production of an enzyme preparation, in accordance with Claim 1 and substantially as described in foregoing 45 Example 6.

17. A process for the production of an enzyme preparation, in accordance with Claim I and substantially as described in foregoing Example 7.

18. A process for the production of an enzyme preparation, in accordance with Claim 1 and substantially as described in foregoing

19. A process for the production of an enzyme preparation, in accordance with Claim 1 and substantially as described in foregoing

20. A process for the production of an enzyme preparation, in accordance with Claim 1 and substantially as described in foregoing

21. A process for the production of an enzyme preparation, in accordance with Claim 1 and substantially as described in foregoing Example 11.

22. A process for the production of an enzyme preparation, in accordance with Claim 1 and substantially as described in foregoing Example 12.

23. A process for the production of an enzyme preparation, in accordance with Claim 1 and substantially as described in foregoing Example 13.

24. An enzyme preparation consisting of uniformly sized solid spheres, which comprises enzyme-containing pellets prepared by spheroidisation of an extrudate of a mixture containing from 75 to 97 per cent of a solid enzyme-containing powder comprising, if desired, an enzyme stabiliser, and from 25 to 3 per cent of water.

FORRESTER, KETLEY & CO., Chartered Patent Agents, Forrester House, 52 Bounds Green Road, London N11 2EY, and

Rutland House, Edmund Street, Birmingham B3 2LD, Agents for the Applicants.

Printed for Her Majesty's Stationery Office by the Courier Press, Learnington Spa, 1974. Published by the Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.